


BCS GT PN VERSO 800

Floor version / Cable



- For installing wall hung standard, extended or compact pan
- Self supporting mounting frame bearing a 400kg load
- Steel tube structure, 30x30x1,5mm, electro-welded and anti-corrosion treated, epoxy paint guaranteed 25 years (withstands 200 hours in saline mist)
- Pan fixing using threaded rods and with possible adjustment after cladding completion.
- Feet are made from one epoxy painted steel plate (180x100x8mm) and one electro-welded epoxy painted steel tubes (25x25x3mm), fixed to the floor with 6 bichromated metal plugs
- 8.5L insulated Verso 800 cistern, from which components can be withdrawn through command plate window
- Adjustable PN 350 simple or double flush pneumatic flush valve, 3L/6L factory preset
- Adjustable noiseless float valve, 6L factory preset
- Simple or double flush pneumatic remote command
- Two meters air hose with corrugated pipe
- Network water connection can be made on the inside or on the outside of the cistern. Stop cock section can be 3/8" M or 1/2" F
- Drainage accessories can be straight or 90° bent. Made from PVC or PEHD. Available sections are 90mm, 100mm and 110mm. Bent pipe is fixed on the frame by simply clipping it
- Cladding reservation and protection accessories



I = 180 mm mini
 II = 100 mm maxi
 III = 20 ~ 60 mm
 IV = 800 ~ 1000 mm
 V = 400 ~ 500 mm
 VI = < 185 mm
 if V = 400 => IV = 200 mm*
 if V = 480 => IV = 120 mm*
 *Depending on the distance in between bowl fixation and top positions

