



BCM 536

Wall mounted version



- For installing wall hung normal length or compact pan
- Wall mounting frame bearing a 400kg load
- Steel tubes structure, 30x30x1,5mm
- Feet are made from one bichromated steel plate (80x30x4mm) and one electro-welded bichromated steel tubes (25x25x4mm), fixed to the floor by 2 plugs and 2 bichromated screw plugs
- Bowl wall fixing thanks to 2 brackets held by 4 plugs and 4 bichromated screw plugs
- Top fixing to the wall using 2 fixing brackets, held in place by 2 plugs and 2 bichromated screw plugs
- 7,5l. cistern, from which components can be withdrawn through command plate window. Cistern insulation is optional
- Adjustable double flush outlet valve, factory preset
- Adjustable hydraulic float valve, factory preset
- Mechanical double or simple flush front commands
- Network water connection can be made on the inside with 3/8th" M stop cock or on the outside of the cistern using 1/2" M connection
- Drainage accessories can be straight or 90° bent. Made from PVC or PEHD. Available sections are 90mm., 100mm. and 110mm.. Bent pipe is fixed on the frame by simply clipping it.
- Pan connection set:
 - Drain straight pipe for connecting pan to bent pipe can be made from PVC or PEHD. Diameter is 100mm
 - Supply straight pipe for connecting cistern to pan
 - Pan fixing accessories
- Cladding reservation and protection accessories are optional

