



BCM INTRASLIM

Wall mounted intraslim



CISTERN :

- Recessed dry wall installation
- Mechanical double or simple flush front commands
- Cistern made from HDPE
- Cistern maximum water volume 7,2l
- Outer EPS insulation
- Adjustable double flush outlet valve, 3l/6l factory preset
- Adjustable noiseless float valve, 6l factory preset
- Isolating valve
- 1/2" M outer water connexion

SUPPORTING FRAME

- For installing wall hung standard, extended or compact bowl
- Wall mounting frame bearing a 400kg load
- Steel tubes structure, 30x30x1,5mm, electro-welded and anticorrosion treated, epoxy paint guaranteed 25 years (withstands 200 hours in saline mist)
- Feet are made from one epoxy painted steel plate (100x30x8mm) and one electro-welded epoxy painted steel tubes (25x25x3mm), fixed to the floor by 2 plugs and 2 bichromated screw plugs
- Pan wall fixing thanks to 2 brackets held by 4 plugs and 4 bichromated screw plugs
- Fixed to the wall using 2 fixing brackets, held in place by 2 plugs and 2 bichromated screw plugs

SUPPLIED ACCESSORIES

- Drain straight pipe for connecting pan to bent pipe can be made from PVC or PEHD diameter is 100mm
- Supply straight pipe for connecting cistern to pan
- Bowl fixing accessories
- Cladding reservation and protection accessories

