

WALL HUNG SANITARYWARE

BCU GT PN VERSO 350
UNIVERSAL VERSION

DESCRIPTION

- For installing wall hung standard, extended or compact pan
- Self supporting mounting frame bearing a 400kg load **NF**
- Steel tube structure **NF**, 45x45x1,5mm, electro-welded and anti-corrosion treated, epoxy paint guaranteed 25 years (withstands 200 hours in saline mist)
- Pan fixing using threaded rods (no need to cut them) and with possible adjustment after cladding completion.
- Feet are made from one epoxy painted steel plate (140x80x8mm) and one electro-welded epoxy painted steel tubes (40x40x4mm), fixed to the floor with 6 bichromated metal plugs. Horizontal mounting frame position adjustment can be made thanks to oblongs holes.
- 6l. insulated Verso 350 **NF** dry riser cistern, from which components can be withdrawn through back removing cover.
- Adjustable PN 350 simple or double flush pneumatic flush valve, 3l./6l. factory preset
- Adjustable noiseless float valve **NF**, 6l. factory preset
- Simple or double flush pneumatic remote command, see choice page 54
- Two meters air hose with corrugated pipe
- Network water connection can be made on the inside or on the outside of the cistern. **NF** Stop cock section can be 3/8" M or 1/2" F.
- Drainage accessories can be straight or 90° bent. Made from PVC or PEHD. Available sections are 90mm., 100mm. and 110mm.. Bent pipe is fixed on the frame by simply clipping it. See choice page 106
- Cladding reservation and protection accessories

	Packing	Packing			Palette Quantity
		Nb	M ³	Kg	
BCU GT PN Verso 350	Carton	1	0,07	19,86	20

SUPPLEMENTS:

Command
Pan connection set
Accessories

(see page 54)
(see page 106)
(see page 106)

