



BCM VERSO 350

Wall mounted version



- For installing wall hung standard, extended or compact pan
- Wall mounting frame bearing a 400kg load
- Steel tubes structure, 30x30x1,5mm, electro-welded and anti-corrosion treated, epoxy paint guaranteed 25 years (withstands 200 hours in saline mist)
- Feet are made from one epoxy painted steel plate (100x30x8mm) and one electro-welded epoxy painted steel tubes (25x25x3mm), fixed to the floor by 2 plugs and 2 bichromated screw plugs
- Pan wall fixing thanks to 2 brackets held by 4 plugs and 4 bichromated screw plugs
- Fixed to the wall using 2 fixing brackets, held in place by 2 plugs and 2 bichromated screw plugs
- 6l insulated Verso 350 cistern, from which components can be withdrawn through command plate window
- Adjustable double flush valve, 3l/6l factory preset.
- Adjustable noiseless float valve, 6l factory preset. Water saving and silent float valve OD 95L as an option
- Mechanical or infra-red double or simple flush front commands
- Network water connection can be made on the inside or on the outside of the cistern. Stop cock section can be 3/8" M or 1/2" F
- Drainage accessories can be straight or 90° bent. Made from PVC or PEHD. Available sections are 90mm, 100mm and 110mm. Bent pipe is fixed on the frame by simply clipping it
- Pan connection set:
 - Drain straight pipe for connecting pan to bent pipe can be made from PVC or PEHD. Diameter is 100mm
 - Supply straight pipe for connecting cistern to pan
 - Pan fixing accessories

