



FIXING INSTRUCTIONS

33/99B PITTA

IMPORTANT

Before starting work please...

- Read carefully these instructions.
- Remove all protection from pottery and check for surface damage or defects as no responsibility can be accepted for obvious defects after installation.
- Check all parts against the parts list.
- Prepare a firm working surface (e.g. floor or bench) for cistern assembly, covering work surface with a cloth to prevent scratching the glazed faces of the cistern.



WARNING

Alterations to these cistern fittings may infringe water regulations and will invalidate our Guarantee

WRAS Approved Inlet Valve COMPACT 99B
WRAS Approved Outlet Flush Valve STORM 33
WC Suite UK Water Supply compliant






PARTS LIST




- ❶ 2 x Cistern fixings
- ❷ 1 x Sealing gasket
- ❸ 1 x Fixing instructions
- ❹ 1 x Inlet valve
- ❺ 1 x Outlet valve
- ❻ 1 x Button
- ❼ 1 x Filter (inlet)
- ❽ 1 x Spanner

ASSEMBLING THE CISTERN



- ❶ Assemble fixing bolts to cistern as shown



- ❷ Assemble outlet valve with washer on the inside of cistern and secure with locking nut

- ❸ Assemble inlet valve with washer on the inside of cistern and secure with backnut, check float moves freely




- ⚠ Please follow the position showed of the inlet valve.






④ Place gasket onto outlet valve



⑤ Secure cistern to WC with locking nuts




⑥ Connect water supply to inlet valve.
N.B. : Make connecting tightness with filter seal.


WARNINGS:

- 1 - Do not overtight in any case.
- 2 - Do not use any sealing paste and/or compound in any case
- 3 - Do not use connector handling the internal part of the inlet valve.

SIAMP will be not responsible in case these warnings are not respected.



⑦ Adjust inlet valve float with screw 'A' to set water line



6L waterline mark



⑧ Assemble push button as shown






SERVICING THE VALVE



Remove valve from cistern as shown



Remove clip and replace the washer

CARE INSTRUCTIONS

Wipe around the pan, cistern, seat & cover with soft damp cloth. DO NOT use scouring powder or abrasive cloths or scourers.

Due to continuing product development we reserve the right to update and amend technical details without prior notice.

For after sales issues
or technical assistance or information,
please contact us at:

**PO Box 155 - ROYDSDALE WAY - EUROWAY - BRADFORD
WEST YORKSHIRE - BD4 6ST**

**RECEPTION TEL: 01274 654 700
CUSTOMER SERVICE FAX: 01274 654 771**

kiwa
approved
product



UK WATER SUPPLY
REGULATIONS

Ref: 50-5598

