

# FIXING INSTRUCTIONS

33/99B SPF JACUZZI

## IMPORTANT

Before starting work please...

- Read carefully these instructions.
- Remove all protection from pottery and check for surface damage or defects as no responsibility can be accepted for obvious defects after installation.
- Check all parts against the parts list.
- Prepare a firm working surface (e.g. floor or bench) for cistern assembly, covering work surface with a cloth to prevent scratching the glazed faces of the cistern.




## WARNING

Alterations to these cistern fittings may infringe water regulations and will invalidate our Guarantee

WRAS Approved Inlet Valve COMPACT 99B  
WRAS Approved Outlet Flush Valve STORM 33A  
WC Suite UK Water Supply compliant

## PARTS LIST




- ❶ 1 x Sealing gasket
- ❷ 1 x Fixing instructions
- ❸ 1 x Inlet valve
- ❹ 1 x Outlet valve
- ❺ 1 x Button
- ❻ 1 x Filter (inlet)
- ❼ 1 x Close coupling plate



## ASSEMBLING THE VALVES




- ❶ Assemble inlet valve with washer on the inside of cistern and secure with backnut, check float moves freely




- ❷ Assemble outlet valve with washer on the inside of cistern with close coupling plate in position and secure with locking nut


- 3** Fitting assembled cistern to Wc pan.  
Before starting check the drawing below for the layout of the components.



- 1 - Valve base
- 5 - Washer
- 6 - Back nut
- 7 - Sealing gasket
- 8 - Fixing plate
- 9 - Bolt
- 10 - Rubber washer
- 11 - Metal washer
- 12 - Wing nut




- The fixing plate (8) should of course already be in the correct position, on the underside of the cistern, held in place by the backnut.
- Place the bolts through the fixing plate, bolt the cistern into place on the pan tail.
- Fit the rubber washer, to protect the ceramic, followed by the steel washers and wingnuts. An effective seal is obviously required but **DO NOT OVERTIGHTEN**.
- A little silicone sealant can be applied if preferred to help guarantee a seal.




- 4** Connect water supply to inlet valve

N.B. : Make connecting tightness with filter seal supplied, do not use corrosive joint compound.



- 5** Adjust inlet valve float with screw 'A' to set water line



6L waterline mark




- 6** Assemble push button as shown

## SERVICING THE VALVE



Remove valve from cistern as shown



Replace the washer

## CARE INSTRUCTIONS

Wipe around the pan, cistern, seat & cover with soft damp cloth. DO NOT use scouring powder or abrasive cloths or scourers.

Due to continuing product development we reserve the right to update and amend technical details without prior notice.

## JACUZZI UK

Bathrooms Product Division

For after sales issues or technical assistance or information, please contact us at:

---

**PO Box 155 - ROYDSDALE WAY - EUROWAY - BRADFORD  
WEST YORKSHIRE - BD4 6ST**

---

**RECEPTION TEL: 01274 654 700 - CUSTOMER SERVICE FAX: 01274 654 771**

---

**kiwa**  
approved  
product



UK WATER SUPPLY  
REGULATIONS