

FIXING INSTRUCTIONS

33/99B

IMPORTANT

Before starting work please...

- Read carefully these instructions.
- Remove all protection from pottery and check for surface damage or defects as no responsibility can be accepted for obvious defects after installation.
- Check all parts against the parts list.
- Prepare a firm working surface (e.g. floor or bench) for cistern assembly, covering work surface with a cloth to prevent scratching the glazed faces of the cistern.



WARNING

Alterations to these cistern fittings may infringe water regulations and will invalidate our Guarantee

WRAS Approved Inlet Valve COMPACT 99B

WRAS Approved Outlet Flush Valve STORM 33


WC Suite UK Water Supply compliant

PARTS LIST



- ❶ 2 x Cistern fixings
- ❷ 1 x Sealing gasket
- ❸ 1 x Fixing instructions
- ❹ 1 x Inlet valve
- ❺ 1 x Outlet valve
- ❻ 1 x Button
- ❼ 1 x Filter (inlet)

ASSEMBLING THE CISTERN



- ❶ Assemble fixing bolts to cistern as shown



- ❷ Assemble outlet valve with washer on the inside of cistern and secure with locking nut

NB : Manually screw the flush valve nut until it is in contact with the ceramic. If necessary give an extra quarter turn (maximum) with the appropriate spanner. Excessive tightening can damage the mechanism and would not be covered by the guarantee.




- ❸ Assemble inlet valve with washer on the inside of cistern and secure with backnut, check float moves freely

NB : Manually screw the backnut until it is in contact with the ceramic. If necessary give an extra quarter turn (maximum).


Excessive tightening can damage the mechanism and would not be covered by the guarantee.



④ Place gasket onto outlet valve



⑤ Secure cistern to WC with locking nuts



⑥ Connect water supply to inlet valve.


N.B. : Make connecting tightness with filter seal.

WARNINGS:


- 1 - Do not overtight in any case.
- 2 - Do not use any sealing paste and/or compound in any case
- 3 - Do not use connector handling the internal part of the inlet valve.

SIAMP will be not responsible in case these warnings are not respected.


An approved double check valve or some other no less effective backflow prevention device shall be fitted at the point of connection(s) between the supply and the fitting.



⑦ Adjust inlet valve float with screw 'A' to set water line



6L waterline mark




⑧ Assemble push button as shown

SERVICING THE VALVE



Remove valve from cistern as shown



Remove clip and replace the washer

CARE INSTRUCTIONS

Wipe around the pan, cistern, seat & cover with soft damp cloth. DO NOT use scouring powder or abrasive cloths or scourers.

Due to continuing product development we reserve the right to update and amend technical details without prior notice.

For after sales issues
or technical assistance or information,
please contact us at:

Style products Ltd

4a Wilsons Park, Monsall Road, Newton Heath, Manchester M40 8WN

Tel : 0161 205 1200 - Fax : 0161 205 1212

kiwa
approved
product



UK WATER SUPPLY
REGULATIONS